



General

Built	February-1992	International	GT 7,743.00	NT 3,726.00
Flag	Bahamas	Panama Canal		6,500.00
Port of Registry	Nassau	Suez Canal		5,953.00
Callsign	C6WH8			
IMO/Lloyds nr	8912132		Draft	DWAT
Length over all [m]	131.27	Tropical	9.03	7,726
Beam [m]	19.60	Summer	8.87	7,721
Depth [m]	12.85	Winter	8.87	7,721
Bowthruster(s)	-			

Reefer

Holds	3
Hatches	3
Compartments	12
Minimum Deckheight [m]	2.20
Allowable weight of forklift including cargo	maximum 7 mt (Forklift to be equipped with minimum 4 airtyres)
Temperature zones	7
Cooling sections	1A 1BC 1D 2AB 2CD 3AB 3CD
Temperature range [dC]	-30/+15
Air circulations [/hr]	90
Air renewals [/hr]	2.4
USDA equipped	Yes, valid until 01-October-2019
Controlled Atmosphere	CA pre-piped
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Det Norske Veritas (DNV)
Class Notation	+1A1 Reefer (-30dC/32dC Sea) Container PET E0

Equivalent Finnish/Swedish Ice Strengthening	-
--	---

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	38,883	442.00	39,660	460.00	38,671	451.00	117,214	1,353.00
B	30,619	356.00	37,647	455.00	38,141	458.00	106,407	1,269.00
C	21,825	263.00	33,338	423.00	30,831	389.00	85,994	1,075.00
D	10,913	137.00	28,111	340.00	27,582	333.00	66,606	810.00
Total	102,240	1,198.00	138,756	1,678.00	135,225	1,631.00	376,221	4,507.00

Hatch sizes

	Hold 1	Hold 2	Hold 3
	l x b	l x b	l x b
Deck	8.33 x 4.68	8.33 x 4.68	8.33 x 4.68
A			
B			
C			

Container Carrying Capacity	Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>				
Empty Positions Standard	45	0	89	4
Max Stackweight Standard	30	0	54	4
Max Stackweight - Self-sustained Standard	30	0	54	4
Empty Positions High Cube	45	0	89	4
Max Stackweight High Cube	30	0	54	4
Max Stackweight - Self-sustained High Cube	30	0	54	4
<u>Reefer Hold</u>				
Empty Positions Standard	0	0	0	0
Max Stackweight - Self-sustained Standard	0	0	0	0
Empty Positions High Cube	0	0	0	0
Max Stackweight - Self-sustained High Cube	0	0	0	0

'Max Stackweight' and 'Max Stackweight - Self-sustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU
Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers	28
of which Selfsustained	28

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs

Nr. of electrical Reefer Plugs	29
--------------------------------	----

Cargo Gear

- 1 Crane x 34.0 mt or 17.0 mt in high speed modus
- 3 Pallet Cranes x 8.0 mt

- All peeds are 'about', all consumptions are 'about', basis clean hull, clean propeller and deep (minimum 7 x deepest draft), currentless water/sea with a temperature of maximum 28 degree Celcius.
- Descriptions are given basis maximum Beaufort 4, maximum 2 meters swell and maximum 2 meters wave height.
- Additional MGO may be used for starting/stopping engines and/or manoeuvring and/or in narrow and/or restricted waters and/or in extreme weather conditions.
- All auxiliary consumptions are based on maintaining cargo temperatures, during reduction period higher consumptions may be recorded.
- All descriptions exclude consumption for carried laden reefer containers. Depending on ao the make and/or type of container, maintenance state of the container, commodity in the container, ambient temperature, use of water cooling, stowage position: as indication an average additional fuel consumption of about 30 kg/container/24hrs when maintaining temperatures to be taken into account.
- Port consumptions are averages for vessel lying alongside berth. Manoevring consumptions are excluded.
- Auxiliary consumption up to 10 mt/day with all generators fully loaded.
- All Speeds are in knots and all consumptions are in metric tons per 24 hours.
- International and/or local regulations may require use of other fuel grades.
- Conditions are based on sailing with even keel, unless stated otherwise. Significant trim, especially large negative trim, may have negative impact on the performance.
- All consumption figures are based on ISO 8217 (latest revision) specification fuels with following minimum caloric values:
HFO: 40.600 kJ/kg
MGO 42.700 kJ/kg

Bunker Tank Capacities

	<u>Cbm (100%)</u>	<u>Cbm at max filling level*</u>	<u>mt**</u>
Bunkertanks dedicated for High Sulphur RMG380 (IFO380)	1,013	861	853
Overflow/Settling/Daytanks for RMG380 (IFO380)	163	110	109
Total bunker capacity for RMG380 (IFO380)	1,176	972	963
Bunkertanks dedicated for Low Sulphur DMA (MGO)	116	98	84
Overflow/Settling/Daytanks for DMA (MGO)	33	28	24
Total bunker capacity for DMA (MGO)	148	126	107

**) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.*

****) Capacity in mt serve as indication only. Actual capacity in mt depending on the specific gravity and temperature of the supplied bunkers.*

Vessel to be solely supplied with fuels as per ISO 8217:2010 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control.

Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."

BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.

If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.

Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's quality.

