



General

Built	June-1994	International	GT 5,471.00	NT 2,978.00
Flag	Dutch	Panama Canal		4,699.00
Port of Registry	Breskens	Suez Canal		4,751.95
Callsign	PDKK			
IMO/Lloyds nr	9085479		Draft	DWAT
Length over all [m]	126.29	Tropical	8.18	7,792
Beam [m]	16.31	Summer	8.01	7,505
Depth [m]	11.90	Winter	7.85	7,221
Bowthruster(s)	1			

Reefer

Holds	4
Hatches	4
Compartments	16
Minimum Deckheight [m]	2.20 (excl local areas).
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equiped with minimum 4 non hard rubber airtyres)
Temperature zones	8
Cooling sections	1A B - 1C D - 2A B - 2C D - 3A B - 3C D - 4A B - 4C D
Temperature range [dC]	-25/+12
Air circulations [/hr]	90
Air renewals [/hr]	2
USDA equipped	Yes, certificate expired
Controlled Atmosphere	CA pre-piped
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +HULL, +MACH
Service Notations	Refrigerated cargo ship
Navigation Notations	Unrestricted navigation
Additional Class Notations	+AUT-UMS, +SYS-NEQ-1, +REF-CARGO, INWATERSURVEY
Machinery	+MACH
Equivalent Finnish/Swedish	
Ice Strenghtening	-

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	23,274	265.80	27,723	327.00	26,416	310.50	24,521	286.60	101,934	1,189.90
B	20,856	231.60	26,964	326.60	25,739	313.40	23,687	288.40	97,246	1,160.00
C	16,400	186.40	25,986	320.00	25,244	314.00	20,539	248.20	88,169	1,068.60
D	13,528	152.60	25,115	300.70	25,001	300.70	11,357	140.30	75,001	894.30
Total	74,058	836.40	105,788	1,274.30	102,400	1,238.60	80,104	963.50	362,351	4,312.80

Hold 1- 4 Legend

Non insulated Deck, air passes through (aka Spar Deck)	Insulated, air tight Deck or Tanktop
Non Insulated, air tight Deck	

Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	8.10 x 8.08	8.10 x 8.08	8.10 x 8.08	8.10 x 8.08
A	8.10 x 7.86	8.10 x 7.86	8.10 x 7.86	8.10 x 7.86
B	8.10 x 7.86	8.10 x 7.86	8.10 x 7.86	8.10 x 7.86
C	8.10 x 5.06	8.10 x 7.86	8.10 x 7.86	8.10 x 7.86

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	31	4	66	0
Max Stackweight	Standard	20	2	42	0
Max Stackweight - Selfsustained	Standard	0	0	0	0
Empty Positions	High Cube	31	4	66	0
Max Stackweight	High Cube	20	2	42	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	40	0
Max Stackweight	Standard	0	0	40	0
Max Stackweight - Selfsustained	Standard	0	0	0	0
Empty Positions	High Cube	0	0	40	0

'Max Stackweight' and 'Max Stackweight - Selfsustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU
Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers 17
of which Selfsustained 0

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs

Nr. of electrical Reefer Plugs 20

Cargo Gear

2 Cranes x 7.0 mt
2 Cranes x 7.0 mt

