



General

			GT	NT
Built	December-1992	International	7,303.00	4,812.00
Flag	Panama	Panama Canal		6,577.00
Port of Registry	Panama	Suez Canal		6,639.00
Callsign	3E3523			
IMO/Lloyds nr	9045168		Draft	DWAT
Length over all [m]	134.02	Tropical	7.73	8,368
Beam [m]	20.80	Summer	7.57	8,075
Depth [m]	10.17	Winter	7.41	7,676
Bowthruster(s)	-			

Reefer

Holds	4
Hatches	4
Compartments	15
Minimum Deckheight [m]	2.20 (excl local areas).
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equipped with minimum 4 non hard rubber airtyres)
Temperature zones	8
Cooling sections	1A - 1B C - 2A B - 2C D - 3A B - 3C D - 4A B - 4C D
Temperature range [dC]	-30/+15
Air circulations [/hr]	90
Air renewals [/hr]	4
USDA equipped	Yes, valid until 09-March-2026
Controlled Atmosphere	None
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +HULL, +MACH
Service Notations	Refrigerated cargo ship
Navigation Notations	Unrestricted navigation
Additional Class Notations	+REF-CARGO
Machinery	+MACH
Equivalent Finnish/Swedish	
Ice Strenghtening	-

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	30,048	340.85	20,569	228.12	20,438	229.59	23,714	267.46	94,769	1,066.02
B	19,090	227.30	30,875	345.89	34,494	371.23	38,662	421.78	123,122	1,366.20
C	13,966	163.27	28,378	340.93	32,265	390.72	31,418	355.05	106,028	1,249.97
D			23,189	270.18	30,328	354.83	23,449	237.07	76,966	862.08
Total	63,105	731.42	103,011	1,185.12	117,525	1,346.37	117,243	1,281.36	400,884	4,544.27

Hold 1- 4 Legenda

Non insulated Deck, air passes through (aka Spar Deck)	Insulated, air tight Deck or Tanktop
Non Insulated, air tight Deck	

Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
A	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
B	7.40 x 4.90	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
C		7.40 x 7.30	7.40 x 7.30	7.40 x 7.30

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	6	0	12	0
Max Stackweight	Standard	6	0	12	0
Max Stackweight - Selfsustained	Standard	0	0	0	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	0	0
Max Stackweight	Standard	0	0	0	0
Max Stackweight - Selfsustained	Standard	0	0	0	0

'Max Stackweight' and "Max Stackweight - Selfsustained" are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU
Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers	6
of which Selfsustained	0

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs

Nr. of electrical Reefer Plugs	12
--------------------------------	----

Cargo Gear

8 Derricks x 5.0 mt or 4 x 3.5 mt in Union Purchase

